
	ETSI BT Power Table							
	Standard:	EN 300 328 v2.1.1	Test Date :	2018/9/7	Test Site:	RF Chamber 2	Test By:	Angus Peng
	Model Name:	BlueX BX2400_B1(CE 委測)					Sample No:	0823-008-006
	Remark:							

Conducted measurement	Extreme test conditions :	Indoor only :	No	Tnormal(℃) :	25	Tmin(℃) :		Tmax(℃) :	
		Power Source :	DC	Vnormal(V) :	4.5				

Mode:		BT LE-GFSK_0dBm port			Data Rate:		1Mbps			Gain(dBi) :			2.16		BF Factor(dB):				
Channel	Freq. (MHz)	Power Setting	Conducted AVG Power (dBm)					EIRP						PSD		Worst Margin (dB)		Bottleneck	
								Tnorm		Tmin		Tmax		Limit (dBm)	dBm /MHz	Margin (dB)	Bandedge		
Chain0				Total	Vnorm	Vnorm		Vnorm											
0	2402	default	-3.03				-3.03	-0.87					20.00	-1.54	-11.54			No, Base on client Spec.	
19	2440	default	-3.13				-3.13	-0.97					20.00	-1.67	-11.67			No, Base on client Spec.	
39	2480	default	-3.44				-3.44	-1.28					20.00	-1.96	-11.96			No, Base on client Spec.	

Note:
 Test Tool: rf_console.exe

 BUREAU VERITAS	ETSI BT Power Table							
	Standard:	EN 300 328 v2.1.1	Test Date :	2018/9/7	Test Site:	RF Chamber 2	Test By:	Angus Peng
	Model Name:	BlueX BX2400_B1(CE 委測)					Sample No:	0823-008-006
	Remark:							

Conducted measurement	Extreme test conditions :	Indoor only :	No	Tnormal(°C) :	25	Tmin(°C) :		Tmax(°C) :	
		Power Source :	DC	Vnormal(V) :	4.5				

Mode:		BT LE-GFSK_8dBm port			Data Rate:		1Mbps		Gain(dBi) :		2.16		BF Factor(dB):					
Channel	Freq. (MHz)	Power Setting	Conducted AVG Power (dBm)					EIRP						PSD		Worst Margin (dB)		Bottleneck
								Tnorm		Tmin		Tmax		Limit (dBm)	dBm /MHz	Margin (dB)	Bandedge	
			Chain0				Total	Vnorm	Vnorm		Vnorm							
0	2402	default	4.91				4.91	7.07					20.00	6.49	-3.51			No, Base on client Spec.
19	2440	default	4.92				4.92	7.08					20.00	6.48	-3.52			No, Base on client Spec.
39	2480	default	4.86				4.86	7.02					20.00	6.41	-3.59			No, Base on client Spec.

Note:
Test Tool: rf_console.exe